SUGGESTED WHEEL WIDTH AND WHEEL BACK SPACE, FOR 55-57 CHEVY CAR, STOCK WIDTH, NARROWED, AND USING POCKET KIT.

STOCK 60" OVER ALL WIDTH, SPRING PADS IN STOCK LOCATION, AT 46" CENTER TO CENTER WIDEST WHEEL, 8" WHEEL WITH 4 ½" WHEEL BACK SPACE.

STOCK 60" OVER ALL WIDTH, SPRING PADS IN STOCK LOCATION, AT 46" CENTER TO CENTER. WIDEST WHEEL, 7" WHEEL WITH 4" WHEEL BACK SPACE.

NARROWED TO 58 ½" OVER ALL WIDTH, SPRING PADS IN STOCK LOCATION, AT 46" CENTER TO CENTER. WIDEST WHEEL, 8" WHEEL WITH 3 ½"/ 4" WHEEL BACK SPACE.

USING POCKET RIT: MOVING SPRINGS IN, TO 38 1/8" CENTER TO CENTER, FROM STOCK, AT 46" CENTER TO CENTER.

NARROWED TO 57" OVER ALL WIDTH, SPRING PADS AT 38 1/8" CENTER TO CENTER, USING POCKET KIT. WIDEST WHEEL, 10" WHEEL WITH 4 ½" WHEEL BACK SPACE.

NARROWED TO 56" OVER ALL WIDTH, SPRING PADS AT 38 1/8" CENTER TO CENTER, USING POCKET KIT. WIDEST WHEEL, 10" WHEEL WITH 4" WHEEL BACK SPACE.

NARROWED TO 52" OVER ALL WIDTH, SPRING PADS AT 38 1/8" CENTER TO CENTER, USING POCKET KIT. WIDEST WHEEL, 10" WHEEL WITH 2" WHEEL BACK SPACE.