

**AMPLIFIED ELECTRONIC AM/FM ANTENNA  
(ACTIVE MAGNETIC TYPE)**

**Designed for optimum AM/FM reception.**

**Excellent for Streetrods Show Cars or any vehicle  
where a conventional is not desirable.**



Before permanently mounting the antenna check different mounting areas for best reception. If vehicle is under a roof it should be moved to an area with a clear view of the sky. Small wire requires 12-volts. This wire should be connected to the auto antenna lead of radio (if radio does not have auto antenna power lead connect to any (switched) 12-volt supply. Antenna plugs into back of your radio.

Antenna body is adhesive backed. Clean mounting area with alcohol and allow to dry before mounting antenna. Cable guide mounts are included with antenna. Use these to secure the cable out of the way clean mounting area as above.

For best performance mount the antenna to the top inside of the windshield. Do not obstruct the antenna by metal as radio waves will not pass through metal. If your dash or roof is fiberglass it is possible to hide the antenna behind these panels. If a windshield mount is not desired the antenna may be mounted on the rear package shelf area. To mount in the rear of vehicle a standard antenna cable extension and 12-volt primary wire may be required to reach your radio.

Antenna and power cable are 104"

Grounding of the antenna is not required as it is grounded through the radio.

**#ANTUV-HIDEAWAY**